

Bid Specification

Video Monitoring and Documentation

SecurityCam Lite

Fast, dependable, solid state Linux operating system

Edge Video Recorder (EVR) - up to 60 days of HD continuous video recording

256bit AES encrypted onboard storage

10/100 ethernet or transmit over 4G networks

All weather dome outdoor enclosure

HDTV 720p resolution
User controllable P/T/Z with multiple preset compositions
21x optical, 12x digital zoom
Continuous 360° pan
Automatic day and night function
Excellent light sensitivity

Specification includes camera system and managed services



Live Streaming Video



User Controllable



Current and Historical Weather Data



iOS and Android App




Multiple Preset Composition



Installation and Maintenance



Quality Control and Maintenance



Full Service Support



Continuous Video Recording

Additional services included



EarthCam.net
The Webcam Technology Experts

1-800-EARTHCAM
www.earthcam.net/contactus



01.32.36 Video Monitoring and Documentation Bid Specification

1. The Contractor shall provide a Robotic Streaming Video Webcam for users to remotely control and view a live feed via a secure connection via a network connection. The camera will provide a full view of the work area on the construction site.

CONTACT SYSTEM VENDOR: EarthCam / Brian Cury +1 201.488.1111 Email: WWW.EARTHCAM.NET/CONTACTUS

2. The camera shall meet or exceed the following requirements:
 - 2.1 Consist of an IP66 weather resistant aluminum housing with an polycarbonate clear dome
 - 2.2 User controllable Pan/Tilt/Zoom controls with multiple preset compositions
 - 2.3 1280x720 (HDTV 720) resolution
 - 2.4 21x optical, 12x digital zoom with 360° continuous pan
 - 2.5 H.264, MPEG-4 Part 10/AVC, Motion JPEG video compression
 - 2.6 Lens: 4.0-84.6mm, F1.6-4.5
 - 2.7 Auto Features: Focus and Day/Night
 - 2.8 Communications: RJ-45 10BASE-T/100BASE-TX PoE
 - 2.9 4G cellular modem
 - 2.10 Secure 128 bit AES encrypted onboard storage
 - 2.11 High-Definition continuous video recording with 60 days of retention (up to 1 year available)
 - 2.12 Industrial grade solid state embedded Linux System
 - 2.13 Power over Ethernet (PoE), max. 20 W
 - 2.14 120VAC, 220-230VAC or 12VDC power
 - 2.15 Designed for EarthCam Control Center Lite
3. Internet Based Online Interface: The camera will be accessible via an internet based Software as a Service (SaaS) solution. This online interface will be managed and supported by the System Vendor. The service will be available for the term of the project and allow the viewing of live video and High Definition digital still images captured and stored of the project on both mobile and desktop platforms.

The Internet Based Online Interface shall include the following features:

- 3.1 Responsive HTML5 design for cross-platform access on desktop and mobile devices
 - 3.2 Secure HTTPS compliant with live stream secured & encrypted via https transport
 - 3.3 Display project name and logo
 - 3.4 Project Dashboard allows easy navigation between multiple cameras and projects
 - 3.5 Security Interface offers flexible multi-view camera grid selective up to 24 cameras per screen streaming simultaneously
 - 3.6 Edge Video Recorder features intuitive visual timeline interface for fast incident footage retrieval and sharing
 - 3.7 Real-time live video viewing with user-controllable Robotic Pan, Tilt and Zoom
 - 3.8 User-controllable settings for creating and editing multiple preset compositions, each preset will be displayed as a thumbnail image
 - 3.9 Instant live snapshot capability in addition to preset scheduled archives
 - 3.10 Visual timeline with quick thumbnail view allows image navigation by year, month, day and hour
 - 3.11 AI-edited time-lapse technology removes frames obscured by foreign objects or weather elements, with music and graphics then added for downloadable presentations
 - 3.12 Full Screen Mode for displaying video and complete image without any graphical frame
 - 3.13 Photo Filters and Graphical Markup Tools for detailing and creating notes with graphical overlays on images, including project title, logo and time date stamp
 - 3.14 Image Comparison Tool for comparing two images taken at different times, overlaid on top of each other
 - 3.15 Project Management Software integration (Autodesk Construction Cloud, Autodesk Build, CMiC, Esri, InEight, Infotech, Procore, Projectmates, Raken, Salesforce)
 - 3.16 3D/4D Model Integration (Autodesk Navisworks, Autodesk Revit, Bentley Synchro)
 - 3.17 Social Media Integration Tools for sharing project images and notes
 - 3.18 Automatically generated daily/weekly project progress update email with camera image and weather
 - 3.19 AI Media Dashboard – Interactive charts display AI-detected events and observations
 - 3.20 Graphical Weather applet displaying local weather data with satellite and updating radar imaging
 - 3.21 Integration of maps, aerial and satellite imagery
 - 3.22 Graphical Data Management Tools showing archived and current system status of solar amperage, battery power remaining, wireless radio connectivity, and device location
4. Access to account protected by Account Security feature which includes four levels of password protection, IP address block/permission and SSL protection of user login password.
 5. The system shall capture and upload images every 1 hour, 24 hours per day.
 6. The system shall have M2M – Machine to Machine 24/7 Support with active self-healing technology and automatic software upgrades to maintain the quality, consistency and reliability of all images.
 7. Images will be maintained on the System Vendor's servers for reference available at all times during the life of the project and for no less than 60 days after completion. All images will be protected on servers owned and operated by the System Vendor and located in a secure area at the System Vendor's location.
 8. The Contractor shall provide all service and maintenance, including cleaning, of the camera system throughout the life of the project including making appropriate arrangements for camera to remain in operation up to and through finalization of all structural, landscaping and "completed state" condition necessary for beginning-to-end record.
 9. The System Vendor shall provide custom public website development. Website shall be separate from the Online Interface, match the look and colors of the project's website, and be delivered as embed code or standalone web page. Additional features include Facebook and Twitter integration, full screen mode, image comparison, weather, multiple logos, graphical background image and project description.
 10. The System Vendor at the end of the project shall provide a comprehensive archive package that includes all images, historical weather data, AI-generated time-lapse movies and a royalty-free web-based viewer software. The software shall include the same interactive interface as the live camera during the project.
 11. The Contractor shall secure a nearby structure for camera mounting or provide a fixed pole (40 foot / 12 meters height recommended) and 3 inch / 8 centimeters minimum diameter as per System Vendor's instruction. The Contractor shall supply all equipment required for safe and secure access to the camera location for technicians performing installation and maintenance services, including building access, bucket truck and/or lift. The System Vendor will consult on and provide recommendations for optimal camera placement and provide professional installation services as required.